MOBILE
POWER ADAPTER

CAR CHARGER 2 USB PORTS

Use

Smartphone/mobile phone, tablet, digital camera, mp3/mp4, GPS device

Main specifications

- Input connector for car/camper
- Input voltage: 12/24Vdc
- Input current: 2A Max
- Two USB output ports to supply 2 utilities in the same time
- Total USB output current: 3,4A Max
- Overload protection
- Short circuit protection

Compatible also with



iPad iPhone

Mobile Power Adapter
Exhibitor WMPTW10

ECO POWER SYSTEM

The Mobile Power Adapter is designed in accordance with the highest environment protection standards.

Italian DESIGN

REFURBISHED COMPONENTS

RoHS COMPLIANT

CE

Specifications

Model	Car Charger 2 USB ports
Code	**FAM17181**
Colour	White
USB Ports	2
Input nominal voltage	12/24 Vdc
Input current	2A Max
Efficiency	>88%
Output voltage	5Vdc
Output voltage range	+/- 0,5Vdc
Total USB output current	3,4A Max
Environmental specification	
Storage temperature	From -15 to 40°C
Working temperature	From 0 to 40°C
Humidity	20-80% (without condensation)
IP protection	IP20
Maximum altitude	3.000 m
Certification	CE
Warranty	
Standard	24 months

© 2014 Tecnoware Power Systems. The technical data can be varied without prior notice.

Use



TECNOWARE
www.tecnoware.com